

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

Rec'd PCT/PTO

K A 44/2
MAR 2005
02


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F16B 21/18, 3/04, 17/00, B60G 7/00		A1	(11) International Publication Number: WO 99/28636
			(43) International Publication Date: 10 June 1999 (10.06.99)
(21) International Application Number: PCT/NO98/00356			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 2 December 1998 (02.12.98)			
(30) Priority Data: 19975563 2 December 1997 (02.12.97) NO			
(71) Applicant (for all designated States except US): KONGSBERG AUTOMOTIVE ASA [NO/NO]; P.O. Box 62, N-3601 Kongsberg (NO).			
(72) Inventors; and (75) Inventors/Applicants (for US only): BJØRKGÅRD, Sven [NO/NO]; Rådmann Friis vei 41, N-3600 Kongsberg (NO). ANDERSEN, Arne [NO/NO]; N-3628 Veggli (NO).			
(74) Agent: ONSAGERS PATENTKONTOR - DEFENSOR AS; P.O. Box 265 Sentrum, N-0103 Oslo (NO).			

(54) Title: DEVICE FOR HOLDING TWO OBJECTS TOGETHER

(57) Abstract

Device for axial retention of a pin (2) in a hole (4). In the wall of the hole (4) there is a groove (8) wherein it is inserted a stopper (10). The pin (2) and an element (20) which may be tightened or pressed axially against an end portion of the pin (2), are near the hole wall provided with mutually opposing edge areas, which are arranged to retain a portion of the stopper which is protruding away from the groove (8) and into the hole (4).



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	JP	Japan	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	KE	Kenya	NL	Netherlands	VN	Viet Nam
CG	Congo	KG	Kyrgyzstan	NO	Norway	YU	Yugoslavia
CH	Switzerland	KP	Democratic People's Republic of Korea	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KR	Republic of Korea	PL	Poland		
CM	Cameroon	KZ	Kazakhstan	PT	Portugal		
CN	China	LC	Saint Lucia	RO	Romania		
CU	Cuba	LI	Liechtenstein	RU	Russian Federation		
CZ	Czech Republic	LK	Sri Lanka	SD	Sudan		
DE	Germany	LR	Liberia	SE	Sweden		
DK	Denmark			SG	Singapore		
EE	Estonia						

Device for holding two objects together

The invention concerns a device for holding together a first and a second object, wherein the first object has a pin, whose free end section projects into a hole of the second object, and the device prevents axial relative movement of the pin in the hole.

From the prior art there are known universal joints with two mutually cooperating joint members, where one joint member comprises a pin which extends into a cylindrical boring of a first, convexly ball-shaped bearing member or cup of this joint member. The second joint member comprises a second, concavely ball-shaped bearing member or cup which is arranged on the outside of the first bearing cup, and which can slide thereon. The first bearing cup is hereby axially secured on the pin via two spring rings, each of which is arranged in its groove in the pin.

On account of the large tolerances required as a result of mounting two spring rings, in this universal joint an axial clearance or play is obtained between the first bearing cup and the pin and thereby impacts between these components, whereby due to the unavoidable wear the play becomes greater. Furthermore, this bearing cup may rotate on the pin, which is usually unintentional, no sliding surface being provided between these parts. A radial wear may thereby also be incurred on cylinder sections of these parts.

It is further known from the prior art that a wheel axle housing for a vehicle can be secured laterally in a chassis of the vehicle by means of a similar universal joint, where a first joint member of the universal joint is securely connected to a section of the axle housing between the wheel and the vehicle, and comprises a pin and a convexly ball-shaped sleeve into which the pin is passed. The universal joint's second joint member is connected to one end section of two arms, each of which extends substantially horizontally and slantingly in its own direction relative to the chassis's longitudinal direction, and whose second end sections are connected to respective, longitudinal chassis beams of the vehicle.

To avoid play between the pin and the sleeve, the pin and the sleeve have conical surfaces and tension elements which are designed complementarily to each other whereby the pin and the sleeve are kept axially pressed together.

However, pins and sleeves designed in this manner are expensive and do not exist in the trade as standardised products.

The object of the invention is to provide a device of the type mentioned in the introduction which can be used for the above-mentioned purpose, but
5 which is not encumbered with the above-mentioned drawbacks.

The characteristics of the device according to the invention are presented in the characteristic features indicated in the claims.

The invention will now be described in more detail with reference to the drawing which schematically illustrates embodiments of a device according
10 to the invention.

Fig. 1 is a longitudinal section through a pin and a sleeve according to a first embodiment of the device according to the invention in its most general form.

Fig. 2 is an enlarged section of an area corresponding to that which is defined
15 by a circle with broken lines in fig. 1, but which illustrates a second embodiment of the device according to the invention.

Fig. 3 is a longitudinal section resembling that shown in fig. 2, but illustrating a third embodiment of the device according to the invention.

Fig. 4 is a perspective view of a section of a vehicle chassis with a universal
20 joint for lateral securing of a wheel axle.

Fig. 5 is a longitudinal section through a universal joint which is illustrated in fig. 4.

As illustrated in fig. 1, a pin 2 is inserted in a boring 4 of a sleeve 6 from one end of the boring 4. In a groove 8 in the boring 4 there is inserted a stopper
25 10 which may be in the form of a short rod which is rectangular in cross section and which may be slightly curved. A first side section 12 of the stopper 10 projects into the groove 8, whereby between the groove 8 and the stopper there may be, e.g., a very snug fit or a tight fit, with the result that there is no clearance between them. In the pin 2 there is provided a central
30 hole 14 which is provided with screw threads.

From the second end of the boring 4 a tension element 20 is inserted therein which is in the form of a plate with a contour corresponding, e.g., to the contour of the pin 2, viewed in the boring's longitudinal direction. Through a central section of the tension element 20 there is provided a boring 22.

5 At opposite edge areas of the tension element 20 and the pin 2 respectively there is provided a recess 24, 26, which together partly engage a second side section 16 of the stopper 10, i.e. the section thereof which projects out of the groove 8 and into the boring 4. Between the tension element 20 and the pin 2 there exists a small clearance A when the pin 2 and the tension element 20
10 abut against the stopper 10 and its second section 16 is received in the recesses 24 and 26.

Through the tension element's boring 22 there is passed a screw 28 which is screwed into the hole 14 of the pin 2, and which is tightened in such a manner that the tension element 20 is pulled forcefully towards the pin 2, and
15 in such a manner that the stopper 10 is firmly secured between them.

When mounting the pin 2 in the sleeve 6 the stopper 10 is first placed in the groove 8. The pin 2 is then inserted in the hole 4 from one end thereof, the second section 16 of the stopper 10 which projects into the hole 4 coming into abutment against the pin 2 in its recess 26. The tension element 20 is
20 then inserted in the hole 4 from the second end and in such a manner that the stopper's second section 16 comes into abutment against the tension element 20 in its recess 24. Thereafter the screw 28 is passed through the boring 22 of the tension element 20 and screwed into the hole 14 of the pin 2 and tightened, with the result that the tension element 20 and the pin 2 come into
25 forceful abutment against the stopper 10. An axial securing of the pin 2 in the sleeve 6 is thereby achieved without play. A relative rotation of the pin and the sleeve can hereby be prevented since the stopper comes into abutment against the end sections of the groove and the recesses.

In fig. 2 a second embodiment of a stopper 30 is illustrated, this too being in
30 the form of a short rod. In this case, however, the groove 32 extends taperingly into the sleeve 6 and the first section 34 of the rod's cross section is formed in a corresponding complementarily tapering fashion. Moreover, recesses 36, 38 of the pin 40 and the tension element 42 are provided as chamfers which extend towards each other and towards the pin's and the

tension element's central section. The second side section 44 of the stopper 30 is formed in such a manner that surface sections thereof remaining lying flat against the respective chamfers 36, 38. Moreover, in this case a screw is also provided for drawing the tension element and the pin together.

- 5 In this second embodiment of the device according to the invention, the stopper is pushed radially outwards, i.e. into the groove 32 when the tension element 42 is forcefully pushed towards the pin 40. The pin 40 is thereby very well secured axially relative to the sleeve, without the need thereby to prepare the groove 32 and the stopper 34 in order to obtain a snug relative fit.
- 10 Furthermore, a relative rotation of the sleeve on the pin is thereby prevented, without play.

- Fig. 3 illustrates a third embodiment of the device according to the invention, wherein there is provided a stopper 50 which is circular in cross section. In the sleeve 52 there is provided a groove 54 with a cross section
- 15 approximately corresponding to a semi-circle, and in a pin 56 and a tension element 58 there are provided recesses 60 and 62 respectively, whose opposite surfaces in cross section are in the form of circular arcs. The diameter of the circle for the groove's cross section may be slightly larger than the diameter of the stopper 50.

- 20 It will be understood that features from the above-described embodiments may be combined and that the grooves and the stoppers may also be designed differently without deviating from the concept of the invention. For example, when using a stopper 50 which is circular in cross section according to the third embodiment of the invention, a groove with slanting surfaces may be
- 25 provided similar to the groove 32 in the second embodiment of the invention, instead of a groove 54 which is semi-circular in cross section.

- Even though it is stated above that the groove in the sleeve is short and the stopper is in the form of a corresponding short rod, it will be understood that the groove may be longer and may, e.g., be circumferential, extending in a
- 30 plane which is perpendicular to the longitudinal axis of the boring 4 in the sleeve 6. The stopper may be designed correspondingly long and possibly as a ring which is split axially, i.e. parallel to an axis which is perpendicular to the plane in which the ring extends. In order for the ring in the latter case to be inserted into the groove, the ring must not be so long that its ends come

into mutual abutment when it is inserted into the groove 8, 32, 54. When the annular stopper is extended between the pin and the tension element, it is expanded and pushed radially outwards in the groove.

5 Fig. 4 is a perspective view of a section of a chassis of a vehicle. Two U-beams 70, 72 of the chassis extend parallel to each other in the vehicle's longitudinal direction. Two arms 74, 76 are each linked by one end section to a beam 70, 72. The arms extend slantingly in relation to the beams and their second end section is securely connected to a joint member of a universal joint 80. The universal joint's second joint member is securely connected to a
10 central section of a wheel axle housing 82 which supports wheels 84.

The invention is specially designed with a view to use in connection with such a universal joint, and an embodiment of this is illustrated in fig. 5.

As illustrated in fig. 5 a pin 90 is made in one piece with a flange 92 via which the pin 90 can be securely connected to the wheel axle housing 82
15 illustrated in fig. 4, e.g. by means of screws (not shown) which can be passed through holes 100. The pin 90 is inserted into a boring 98 of a sleeve-shaped, inner bearing cup 94 with an outer surface 96 which is designed as a section of a surface of a ball. In the boring 98 there is provided a circumferential groove, which is approximately semi-circular in cross section, in which there
20 is inserted a wire ring, whose wire cross section is approximately correspondingly circular. A tension element 102 is tightened or pressed towards this by means of a screw 104 which is screwed into a hole in the pin 90. The wire ring is thereby clamped between the pin and the tension element and hereby forced radially outwards relative to the boring 98 and into the
25 groove, thus preventing an axial movement of the bearing cup 94 relative to the pin 90 as well as a relative rotation of these parts.

Radially outside the bearing cup 94 there is provided an outer bearing cup 106 complementarily formed in relation thereto, which cup is axially secured in an associated housing 108 which in turn is connected to the second end
30 sections of the arms 74, 76.

Thus with this universal joint no shoulders, rings or the like require to be provided on the pin against which the housing 108 can abut when it is tilted relative to the pin 90, with the result that the housing's maximum tilting angle can be large. Moreover, the transitional section between the cylindrical

pin section and the flange 92 can be without notch-forming sections, thus avoiding tension concentrations which can easily lead to cracks in the pin. Since the device permits the use of an inner bearing cup with a cylindrical boring, cheap, standardised ball joints which exist in the trade can be employed.

PATENT CLAIMS

1. A device for holding together a first and a second object, wherein the first object has a pin (2;40;56;90), whose free end section projects into a hole (4;98) of the second object, and the device impedes axial relative movement of the pin (2;40;56;90) in the hole (4;98), where there is provided in the hole wall a groove (8;32;54) extending along a transverse plane in relation to the hole's (4;98) longitudinal axis, in which groove there is inserted a stopper (10;30;50) with a first section (12;34) which projects into the groove (8;32;54) and a second section (16;44) which projects away from the groove (8;32;54) and into the hole (4;98), characterized in that the groove (32;54) is tapering in the direction away from the hole (98) and that the first object comprises an element (20;42;58) which may be tightened axially towards the end section, and the pin (2;40;56;90) and the element (20;42;58) which may be tightened near the hole wall have mutually opposing edge areas, which are arranged to abut against and by drawing together the element (2;42;58) and the pin (2;40;56;90), to securely clamp between them the second section (16;44) of the stopper (10;30;50), at least one of the edge areas being chamfered in such a manner that it extends away from the opposite edge area and towards the hole wall, when the pin (40;56;90) and the element (42;58) are disposed in the hole.
2. A device according to claim 1, characterized in that the hole (4;98) and the pin (2;40;56;90) are cylindrical, the groove (8;32;54) extends round the hole's (4;98) longitudinal axis and in a plane which is perpendicular to the hole's longitudinal axis, and is semi-circular in cross section, and the stopper (10;30;50) is a wire ring which is round in cross section and extends along a circle in a ring plane, radially expandable in its ring plane.
3. A device according to claim 2, characterized in that the wire ring is C-shaped, i.e. axially split at a point along its periphery, whereby its ends do not come into contact with each other when it is inserted into the groove (8;32;54).

4. A device according to one of the preceding claims,
characterized in that the element (20;42;58) which may be tightened is a
plate with a contour corresponding to the contour of the pin (2;40;56;90), the
pin (2;40;56;90) has an axially extending hole (14) which is open at the pin's
5 free end and which is provided with screw threads, the element (20;42;58)
has an axial hole through which there extends a screw (28) with a head which
abuts against the element (20;42;58), and a threaded section which is screwed
into the hole (14) of the pin (2;40;56;90).

5. A device according to one of the preceding claims, where the objects
10 are components of a first, inner joint member of a universal joint (80)
comprising mutually cooperating joint members with respective,
complementarily formed ball surface areas,
characterized in that the outer surface of the second object is convex and is in
the form of a part of a ball surface (96).

15 6. A device according to claim 5,
characterized in that the universal joint (80) connects arms (74,76) which are
connected to a chassis (70;72) of a vehicle, with a wheel axle (82) of the
vehicle for lateral securing of an axle (82) relative to the chassis (70;72).

1/2




Fig. 1




Fig. 2




Fig. 3

2/2




Fig. 4




Fig. 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00356

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F16B 21/18, F16B 3/04, F16B 17/00, B60G 7/00
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F16B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4225263 A (ASBERG), 30 Sept 1980 (30.09.80), column 3, line 23 - line 33, figure 3	1-4
A	--	5,6
X	US 3374015 A (P.E. GIES), 19 March 1968 (19.03.68), see figure 3 and reference number 15 and 16	1-4
A	--	5,6
A	US 3832076 A (GEHRKE), 27 August 1974 (27.08.74), see figure 2, reference number 24	1
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 February 1999

Date of mailing of the international search report

10 -03- 1999

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Marita Öun
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00356

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0633128 A1 (SULZER ESCHER WYSS GMBH), 11 January 1995 (11.01.95), figure 1 --	1
A	US 5092704 A (BUHL ET AL), 3 March 1992 (03.03.92), figure 1 -- -----	1

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/02/99

International application No.
PCT/NO 98/00356

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4225263 A	30/09/80	FR 2385934 A,B GB 1571477 A JP 53122056 A JP 58053208 B SE 399745 B,C	27/10/78 16/07/80 25/10/78 28/11/83 27/02/78
US 3374015 A	19/03/68	NONE	
US 3832076 A	27/08/74	AR 196153 A AU 464871 B AU 5925073 A BR 7307236 D CA 982355 A DE 2342940 A FR 2200453 A,B GB 1387576 A JP 49070048 A	30/11/73 11/09/75 20/02/75 00/00/00 27/01/76 18/04/74 19/04/74 19/03/75 06/07/74
EP 0633128 A1	11/01/95	DE 4322724 A,C DE 59406957 D	12/01/95 00/00/00
US 5092704 A	03/03/92	DE 3930741 C EP 0417663 A,B SE 0417663 T3 ES 2044355 T JP 1948854 C JP 3276876 A JP 6078071 B KR 9404723 B	13/12/90 20/03/91 01/01/94 10/07/95 09/12/91 05/10/94 28/05/94

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.